

WoodLux Herringbone

Technical Data

Board Construction:




3mm Oak Top Layer

9mm Multiply Core

Fixed Length Boards

600mm

150mm



Product Specification:

Board Depth:	12mm
Board Width:	150mm
Board Length:	600mm
Pack Size:	2.16m ²
Pack Weight:	17kg
Packs Per Pallet:	36

Manufacturer Testing Standard:

Standard:	EN14342:2013 - Multiply Flooring Board
Reaction to Fire:	Dfl - s1
Minimum Density:	620 kg/m ³
Minimum Thickness:	12mm
Formaldehyde:	E-1
Thermal Conductivity:	0.12 W/mK
Biological Durability:	Class 1

Board Detail:

Type of Board:	Engineered Wood Flooring
Finish:	Brushed & Matt Lacquered
Bevel Detail:	4V Bevel
Density of Finish:	150g/m ²
Fix System:	Clic
Grade:	Rustic
Core Material:	Eucalyptus & Poplar
Janka Reading:	NPD

Additional Information:

Residential Warranty:	15 Years	
Commercial Warranty:	5 Years	
Oak Origin:	Europe	
Manufactured In:	PRC	
Installation Type:	X	Float
	☒	Bond
	X	Nail
Underfloor Heating:	Suitable for UFH if installed as floating floor with DPM underlay. - Manifold temp must not exceed 26°C	

Key Features:



Accreditations:

